

"All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. The results reported herein are based solely on the limited sample provided to us for testing under laboratory conditions and are NOT intended to be representative of typical product performances.

3M shall not be liable in tort or in contract for any injury, loss or damage, direct, indirect, special or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for user's intended use, and user assumes all risks and liability whatsoever in connection therewith."

### 3M 255L Gold Film

Product	255L
Construction	P-graded Aluminum Oxide is coated on a durable film backing with a resin bond. A Frecut™ treatment is applied. Grades available are P80, P100, P120, P150, P180, P220, P240, P320, P400 and P500. It is available in both Stikit™ and Hookit™ formats.
Application Areas	This product is very effective in the sanding of paint, wood, fiberglass, and plastics.
Features	Contains a proprietary Frecut™ coating to resist loading.
Max. Available Width	51 in (1295.4 mm)

### Available Converted Forms (\*)

#### Belts

Regular  
Segment  
Clipped

#### Discs

\* Regular  
Roloc™  
Delappe  
Overlap slotted

#### Evenrun

Bands  
Belts

#### Rolls

\* Regular  
Scored  
Serrated  
Slit down  
Cartridge

#### Stikit™

\* Disc/roll  
Sheet/roll  
Refill rolls  
Individual discs  
Individual sheets

#### Other

PG wheels  
RX segments  
Slashed assemblies  
Sheets  
Cones