

"All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. The results reported herein are based solely on the limited sample provided to us for testing under laboratory conditions and are NOT intended to be representative of typical product performances.

3M shall not be liable in tort or in contract for any injury, loss or damage, direct, indirect, special or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for user's intended use, and user assumes all risks and liability whatsoever in connection therewith."

3M 300D Stikit™ Three-M-ite™ Resin Bond Cloth

Product	300D
Construction	P-graded Aluminum Oxide mineral in all but grade 80. Backing is J weight Resin Bond Cloth. The abrasive side colour is brown. Grades available are 80, P100, P120, P150, P180, P220, P240, and P320. Open coat construction
Application Areas	Used in disc and roll form. Hardwoods, softwoods, and metals. Dry use only.
Features	A very versatile Stikit™ product, where edge durability is a critical concern. Good durability and excellent cut. Discs are provided with a solid liner or non-linered disc rolls.
Max. Available Width	12 in (304.8 mm)

Available Converted Forms (*)

Belts	Discs	Evenrun
Regular	Regular	Bands
Segment	Roloc™	Belts
Clipped	Delappe	
	Overlap slotted	
Rolls	Stikit™	Other
* Regular	* Disc/roll	PG wheels
Scored	* Sheet/roll	RX segments
Serrated	Refill rolls	Slashed assemblies
Slit down	* Individual discs	Sheets
Cartridge	* Individual sheets	Cones