

"All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. The results reported herein are based solely on the limited sample provided to us for testing under laboratory conditions and are NOT intended to be representative of typical product performances.

3M shall not be liable in tort or in contract for any injury, loss or damage, direct, indirect, special or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for user's intended use, and user assumes all risks and liability whatsoever in connection therewith."

### **3M 415U/415N Tri-M-ite™ Frecut™ Paper**

<b>Product</b>	415U/415N
<b>Construction</b>	ANSI graded Silicon Carbide mineral. Backing is a modified A weight paper. The abrasive side colour is white. 415U grades available are 80, 100, 120, 150, 180 and 220. 415N grades available are 240, 280 and 320. The product is supersized with a loading resistant coating. The 415U product is resin bonded, and the 415N is glue bonded. Open coat construction.
<b>Application Areas</b>	Used in disc and sheet form for light portable machine and hand sanding. Hardwoods, softwoods, plastics, paints and primers. Dry use only.
<b>Features</b>	Our most universally accepted woodworking product for sealer sanding. Highly reliable and consistent. Good durability and excellent cut.
<b>Max. Available Width</b>	45 in (1143 mm)

### **Available Converted Forms (\*)**

<b>Belts</b>	<b>Discs</b>	<b>Evenrun</b>
Regular	* Regular	Bands
Segment	Roloc™	Belts
Clipped	Delappe	
	Overlap slotted	
<b>Rolls</b>	<b>Stikit™</b>	<b>Other</b>
* Regular	* Disc/roll	PG wheels
Scored	* Sheet/roll	RX segments
Serrated	* Refill rolls	Slashed assemblies
Slit down	* Individual discs	* Sheets
Cartridge	Individual sheets	Cones