



Lift-up fitting for kitchen appliances



The parallel-lift-up fitting for kitchen appliances swings out of the base cabinet and into its final position flush with the work surface and securely locked in position by a safety device. For unlocking and swing-in-procedure, safety trigger has to be released with both hands. A tension spring provides for easy operation. The Lift-up fitting is suitable for installation in cabinets with an inside width from 276 mm (10 7/8") to 581 mm (22 7/8").

A double spring version is available for heavier loads. The counter balance lifting capacity is 8 to 16 lbs. (1 or 2 springs), with single springload capacity 8 lbs. while in lifting motion/25 lbs. locked in final position, with double springload capacity 16 lbs. while in lifting motion/25 lbs. locked in final position.

	Ref. No	Finish	
1128.06			
with single spring	498.112.80.2.51	white	epoxy coated
128.07			
with double spring	498.112.80.4.51	white	epoxy coated

 1 pce.	<u>1</u>
 5 pcs.	<u>0</u>

Built-in ironing board



The MEPLA ironing board incorporates a unique automatic lift mechanism and a positive lock. The lock holds the work surface firmly against the countertop edge for excellent stability.

Suitable for standard 18" cabinets. Two spacers are included. For special cabinet size, install without spacers or with custom mounting blocking.

Ref. No.	
499.050.39.0001	Ironing board
499.050.39.0002	Heat reflecting replacement cover

**Lift-up fitting
Ironing board**

